

Automatic single distillation water distiller with built-in storage tank

Liston A 1104



Features:

- Modern all-in-one design
- Low cost, comparing to competitors and distiller + separate automatic tank systems
- Electronic control system (automatic water and power cut-off when tank is full and automatic start, after distillate is taken from tank)
- Electronic leakage-proof safety system with solenoid valve
- Thermostatic low-water cut-off safety system
- Easily accessed evaporator, condenser-tank for effortless maintenance (cleaning, etc.)
- Easily replaceable condenser
- Easily accessible control unit with possibility to be replaced without disassembling the distiller itself
- All parts for installation included (Ready for use out of the box)

Technical specifications

Distilled water production (capacity)	4 liters per hour
Storage tank volume	8 liters (2 hours of work)
Water consumption	70 liters per hour (17.5 liter per 1 liter of distillate)
Energy consumption	0.75 kW/h per 1 liter of distillate (3 kW per hour)
Distillate conductivity	2,5 μ S/cm (depends on quality of incoming water)
Material	Stainless steel (AISI 321 – internal parts, that have contact with water and steam, AISI 430 – outer body)
Dimensions (WxLxH)	620x320x490 mm
Weight	25 kg
Power supply	230 Volts / 60 Hz, 3kW, single phase

Manufacturer: Liston, LLC, 249037, Shatskogo street, 14, Obninsk, Kaluga region, Russian Federation

ISO 13485:2003 certificate № QM-0090-130380 from 22 of August 2014 issued by TCS Certification (regular inspection protocol IEC #258/12359.18 – confirmed the standards)

CE attestation of conformity № M.2015.103.5094 issued by UDEM International Certification

Liston A 1104 automatic distiller set includes:

1. Distiller
2. Water supply hose with connector, 2 gaskets and clamp
3. 2 Drain hoses (1 for dump water and for cleaning procedure) with connectors and clamps
4. Silicone tube with clamp for distillate

C.E.O. Liston, LLC



Roman Saprygin