

Single distillation water distiller

Liston A 1204



Features:

- Modern space saving design
- Low-cost
- High-quality distillate - conductivity approximately 2,5 $\mu\text{S}/\text{cm}$ (depends on incoming water)
- Thermostatic low-water cut-off safety system
- Heaters made of stainless steel with extended resource
- Easily accessed evaporator, condenser-tank for effortless maintenance (cleaning, etc.)
- All parts for installation included (ready to use out of the box)

Technical specifications

Distilled water production (capacity)	10 liters per hour
Water consumption	150 liters per hour (15 liters per 1 liter of distillate)
Energy consumption	0.75 kW/h per 1 liter of distillate (7.5 kW per hour)
Distillate conductivity	2,5 $\mu\text{S}/\text{cm}$ (depends on quality of incoming water)
Material	Stainless steel with powder coating (AISI 321 – for parts that contact water and steam, AISI 430 – for “dry” lower part of the body)
Dimensions (WxLxH)	410x460x610 mm
Weight	19 kg
Power supply	380 Volts / 60 Hz, 7.5 kW, three phases

Manufacturer: Liston, LLC, 249037, Shatskogo street, 14, Obninsk, Kaluga region, Russian Federation

ISO 13485:2003 certificate № QM-0090-130380 from 22 of August 2014 valid until 21 of August 2015 issued by TCS Certification

CE attestation of conformity № RU-MD-1344 from 14 of August 2014 valid until 20 of August 2015 issued by TCS Certification

Liston A 1204 automatic distiller set includes:

1. Distiller
2. Flexible metal water supply hose with manual ball valve
3. Metal pre-filter for connection point
4. 2 drain hoses (1 for dump water and 1 for cleaning procedure) with connectors and clamps
5. Silicone tube with clamp for distillate

C.E.O. Liston, LLC



Roman Saprygin